
Nec 80573 User Guide

*Downloaded
from
old.setefer.com
by Fields
Becker*

**Nec 80573
User Guide**

INTRODUCTION TO THE NEC 80573 USER GUIDE

When you invest in professional-grade display equipment, having a reliable reference document is essential. The **Nec 80573 User Guide** serves as the definitive resource for setup, operation, troubleshooting, and maintenance of this specific NEC model. Whether you are an IT administrator deploying displays

across a corporate campus, an educator integrating visual technology into the classroom, or a home theater enthusiast seeking optimal picture quality, this guide will walk you through every critical aspect. Understanding the features and functions outlined in your user manual not only extends the lifespan of your equipment but also ensures you extract maximum performance from day one.

NEC has built a strong reputation for producing durable, high-performance

monitors and projectors. The model associated with the **Nec 80573 User Guide** is no exception. It combines advanced imaging technology with intuitive controls, making it suitable for both professional and personal use. However, like any sophisticated piece of electronics, proper configuration requires careful attention. This article provides a comprehensive, user-friendly walkthrough that complements your official documentation. Let us begin with an overview of what to expect when you first unbox your unit.

WHAT IS THE NEC 80573? A QUICK OVERVIEW

Before diving into step-by-step instructions, it helps to understand

the product itself. The NEC 80573 is a display device designed for high-resolution output. It is commonly used in conference rooms, control centers, and digital signage applications. The **Nec 80573 User Guide** typically covers hardware specifications, input and output ports, on-screen display menus, and recommended operating conditions. Key features often include multiple connectivity options such as HDMI, DisplayPort, USB-C, and VGA, as well as integrated speakers and advanced calibration tools. This model supports resolutions up to 4K, depending on the specific variant, making it suitable for detailed presentations,

data visualization, and multimedia playback.

Whether you are setting up a single monitor or a multi-display wall, the procedures remain consistent. The following sections will guide you through the entire user experience, from initial unpacking to advanced settings.

UNBOXING AND PHYSICAL SETUP

What Comes in the Box

When you open the packaging, the **Nec 80573 User Guide** recommends verifying that all components are present. Typical contents include:

- The NEC display unit
- Power cable (region-specific)
- Video cables (HDMI or DisplayPort)
- Remote control with batteries
- Stand or mounting bracket hardware
- Quick start guide and safety booklet

If any item is missing or damaged, contact your authorized NEC dealer before proceeding. Keeping the original packaging is advisable in case you need to transport the unit later.

Choosing

the Right Location

Placement significantly affects performance. The **Nec 80573 User Guide** advises selecting a location that meets the following criteria:

- A stable, level surface free from excessive vibration
- Proper ventilation: allow at least 10 cm of clearance on all sides
- Away from direct sunlight, heat sources, and high humidity
- Accessible power outlet with surge protection

For wall mounting, use a VESA-compatible bracket rated for the

weight of the display. The VESA pattern is typically 400 x 400 mm for this model, but always confirm in your specific user manual. Ensure the wall can support the combined weight of the bracket and the display.

Connecting the Display

Once the display is positioned, it is time to connect your devices. The **Nec 80573 User Guide** provides detailed port maps, but the general procedure is as follows:

1. Connect your video source (laptop, desktop, media player) using HDMI or DisplayPort. For

ON-SCREEN

For video services, VGA or DVI adapters may be needed.

2. If using USB-C, ensure the cable supports video transmission and sufficient power delivery for your source device.
3. Plug the power cable into the display and then into a grounded outlet.
4. Press the power button on the display or remote control.

If no image appears, verify that the correct input source is selected using the Source button on the remote or the OSD (On-Screen Display) menu.

NAVIGATING THE

DISPLAY MENU

Accessing the Menu

The OSD is your primary interface for adjusting picture settings, audio, and system preferences. Press the Menu button on the remote control or the joystick located on the back or bottom bezel of the display. The **Nec 80573 User Guide** divides the OSD into logical sections such as Picture, Audio, PIP/PBP, Setup, and Advanced. Navigation is straightforward: use directional buttons or the joystick to move through options, and press Enter to select.

Key Picture Settings

For optimal image quality, focus on these adjustments:

- **Brightness:**
Controls the black level.
Adjust until black areas appear deep without losing detail in shadows.
- **Contrast:**
Adjusts white level. Set so that white areas are bright but not clipped.
- **Sharpness:**
Enhances edge detail. Avoid setting too high, as it introduces artifacts.
- **Color**

Temperature:

Choose from presets like Warm, Normal, Cool, or Custom for fine RGB balance.

- **Gamma:** Affects mid-tone brightness. A gamma of 2.2 is standard for most environments.

The **Nec 80573 User Guide** also includes specific calibration values for sRGB, DCI-P3, and other color spaces. If you work in graphic design or video production, using a hardware calibrator in conjunction with the internal color management system yields the most accurate results.

Audio Configura tion

Built-in speakers are convenient, but they may lack depth for critical listening. In the Audio menu, you can adjust volume, enable or disable the internal speakers, and select the audio input source if using HDMI ARC. If you connect external speakers via the audio output jack or digital optical port, the guide recommends disabling internal speakers to prevent interference.

PIP and PBP

Modes

Picture-in-Picture and Picture-by-Picture modes allow you to display content from two sources simultaneously. This is useful in control rooms or for comparing data. The **Nec 80573 User Guide** explains how to assign sources, resize the secondary window, and swap audio priority. Note that higher resolutions may limit PIP functionality due to bandwidth constraints.

ADVANCED FEATURES AND CALIBRATION

Color

Management System

Input Lag and Response Time

Professional users will appreciate the Color Management System (CMS). This feature lets you adjust hue, saturation, and gain for each primary and secondary color independently. The **Nec 80573 User Guide** provides step-by-step instructions for accessing the CMS through the Advanced Picture menu. For best results, use a spectrophotometer and calibration software. Save your calibrated profile to one of the available picture memory slots for quick recall.

For gaming or interactive applications, low input lag is crucial. The display includes a dedicated Game mode that reduces processing overhead. The **Nec 80573 User Guide** reveals that enabling Game mode can lower input lag to under 10 ms. Additionally, you can adjust response time settings to reduce ghosting. Standard, Fast, and Faster options are available. Fast is generally sufficient for most content without

introducing overshoot artifacts.

USB Hub and Firmware Updates

Your NEC 80573 likely includes a built-in USB hub for connecting peripherals like keyboards, mice, or webcams. The **Nec 80573 User Guide** explains that the upstream USB port must be connected to your computer for the hub to function. To update the display firmware, visit the NEC support website, download the latest firmware file, and follow the update utility instructions provided in the

manual. Keeping firmware current ensures compatibility with new devices and fixes known issues.

TROUBLESHOOTING COMMON ISSUES

No Display or Blank Screen

If the screen remains black after powering on, check these items in order:

1. Ensure the power cable is securely connected and the outlet is live.
2. Verify that the display is powered on (look for the standby LED).

3. Confirm the correct input source is selected.
4. Test with a different cable or source device.

The **Nec 80573 User Guide** also suggests performing a factory reset via the OSD if the problem persists. To do this, navigate to Setup > Reset and select Factory Default.

Image Flickering or Distortion

Flickering often results from incompatible refresh rates or faulty cables. Set your source to output the native resolution of the

display, typically 3840 x 2160 at 60 Hz. Use high-speed HDMI cables certified for 4K. If using a long cable run, consider an active repeater or fiber optic cable. The **Nec 80573 User Guide** notes that electromagnetic interference from nearby equipment can also cause distortion. Move the display away from large transformers or wireless routers.

Remote Control Not Responding

Before assuming the remote is defective, replace the batteries

with fresh ones and ensure nothing is blocking the infrared sensor on the display. The **Nec 80573 User Guide** lists compatible remote codes if you are using a universal remote. Pairing instructions are provided in the Setup section. If the remote still does not work, you can use the joystick on the display to navigate all menus.

Fan Noise and Heat

Some models incorporate cooling fans that may become audible in quiet environments. The **Nec 80573 User Guide** advises checking that the ventilation grilles are not blocked. Clean them periodically with a soft brush or

compressed air. If fan noise is excessive, it may indicate a hardware fault. Contact NEC support for further assistance.

MAINTENANCE AND CARE

Cleaning the Display Surface

To maintain image clarity, clean the screen regularly. The **Nec 80573 User Guide** provides these guidelines:

- Turn off the display and unplug it before cleaning.
- Use a soft, lint-free microfiber

cloth slightly dampened with distilled water.

- Do not apply liquids directly to the screen; spray the cloth first.
- Avoid ammonia-based cleaners, alcohol, or abrasive materials.
- For stubborn smudges, use a screen-cleaning solution recommended by NEC.

Ventilation and Dust Control

Dust accumulation inside the display can reduce cooling efficiency. The **Nec**

80573 User Guide

recommends periodic inspection of the ventilation openings. If you operate the display in a dusty environment, consider using a filtered air intake or scheduling professional cleaning every 6 to 12 months. Ensure the display is mounted with adequate airflow around the rear panel.

Transport and Storage

If you need to move the display, always use the original packaging or a padded case. The **Nec 80573 User Guide** warns against stacking other items on top of the screen and advises storing it in a

cool, dry place with a temperature range of -20°C to 60°C. Before long-term storage, remove the batteries from the remote control to prevent leakage.

FREQUENTLY ASKED QUESTIONS

Can I Daisy-

Chain Multiple NEC 80573 Displays?

Yes, if your model supports DisplayPort Multi-Stream Transport (MST). The